

20

25

WHAT IS CLAIMED IS:

- 1. A group III nitride compound semiconfuctor light-emitting device, comprising:
- a semiconductor laminate portion including a 5 light-emitting layer; and

a reflection surface disposed so as to be opposite to a side surface of said semiconductor laminate portion, wherein said semiconductor laminate portion and said reflection surface are provided in one and the same chip.

- 2. A group III nitride compound semiconductor light-emitting device according to claim 1, wherein said reflection surface reflects light from said side surface of said semiconductor laminate portion into a direction of an optical axis of said light-emitting device.
- 3. A group III nitride compound semiconductor light-emitting device according to claim 1, wherein a distance between said reflection surface and said side surface of said semiconductor laminate portion is in a range of from 0.1 to 10 μm .
- 4. A group III nitride compound semiconductor light-emitting device according to claim 1, wherein said reflection surface is made of a material which is the same as

20

5

that of an n pad electrode .

- 5. A group III nitride compound semiconductor light-emitting device according to claim 4, wherein a portion of said n pad electrode opposite to said side surface of said semiconductor laminate portion forms a second reflection surface.
- 6. A group III nitride compound semiconductor light-emitting device according to claim 4, wherein said reflection surface is formed on an n-type semiconductor layer which is formed by etching to be a first depth, and said n pad electrode is formed on said n-type semiconductor layer which is formed by etching to be a second depth shallower than said first depth.
- 7. A group /III nitride compound semiconductor light-emitting device according to claim 4, wherein said reflection surface is formed integrally with said n pad electrode.
- 8. A group III nitride compound semiconductor light-emitting device, comprising:
- a laminate of group III nitride compound semiconductor
 25 layers inclusive of a light-emitting layer;

25

a groove formed in said laminate; and a reflection surface formed on an outer side surface of said groove.

- 9. A group III nitride compound/semiconductor light-emitting device according to claim 8, wherein said groove is formed by a dicing saw.
 - 10. A group III nitride compound semiconductor light-emitting device according to claim 8, wherein said reflection surface is made of a metal layer.
 - 11. A group III nitride compound semiconductor light-emitting device according to claim 10, wherein said metal layer is made of a material which is the same as that of an n pad electrode, and said metal layer is formed at the same time when said n pad electrode is formed.
- 12. A group III nitride compound semiconductor

 20 light-emitting device according to claim 8, wherein light
 emitted from a side surface of said laminate is reflected by
 said reflected surface in a direction of an optical axis of
 said light-emitting device.
 - 13. / A group III nitride compound semiconductor

light-emitting device according to claim 8, wherein said groove has a depth to reach a substrate.

14. A group III nitride compound semiconductor

5 light-emitting device according to claim 8, wherein said groove is substantially parallel to a chip cutting line.